

# BUS.2250



## 2250 LITRE BUNDED STEEL OIL TANK



### TANK:

The inner tank provides the required storage area, the outer tank forms the required bund with capacity for 110% of the total liquid being stored. The tank is suitable for storage of Diesel, Kerosene and certain other oils. Please check before usage.

### THIS TANK COMPLIES WITH:

Oil Pollution Prevention Guidelines (England and Wales) 2002 PPG2. BS799 pt5

### SPECIFICATIONS:

- Tough Steel construction
- 2250 litres (495 galls) capacity
- 3 No. 2" top sockets (for fill, vent & spare)
- 1 No. 1 1/2" top socket (for tank & bund gauge)
- 1 No. 1" bottom outlet socket

- 1 No. 1" top suction drain socket (plugged)
- 1 No. 2" tank to bund vent
- Tank contents gauge (optional extra)
- Outlet filter kit (optional extra)
- Mounted on 100mm x 50mm high channel support bearers
- 10 year warranty

### DIMENSIONS:

Length: 1830mm  
 Width: 1220mm  
 Height: 1220mm  
 Weight: 370kg



# BUNDED STEEL TANK

## EQUIPMENT OPTIONS

### TANK CONTENTS GAUGES:



Clock Face  
GA.CG.4



Spiral Float\*  
GA.F2.4



Sonic Visual  
GA.AP.VI



Sonic Smart  
GA.AP.SM

### OUTLET FILTER KITS:



Advanced  
AC.TFK.A



90°  
AC.TFK.90



90° Tee  
AC.TFK.90T



Parallel Tee  
AC.TFK.PT



Straight Tee  
AC.TFK.ST



Parallel Tee 3 Gang  
AC.TFK.PT.3



Parallel Tee 4 Gang  
AC.TFK.PT.4

### SECURITY OPTIONS:



Locking Lid  
EXT.LID



Spin Secure Tank Lock  
TL.020

\*Model dependant

**EasyTANK**